



Energetic Lighting's surface mount wrap light delivers a soft light profile to brighten up any application. Available in a 2-ft length, this versatile light can be used for general room lighting, or as a functional work area light. Installation is quick and simple when mounting into standard ceiling junction boxes. Constructed with a durable aluminum housing body and LED lifetime rating of at least 50,000 hours, this rugged wrap light is designed for many years of reliable operation.

## **Features**

- No UV or IR radiation
- Modern and efficient design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation

## **Applications**

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- General lighting











Other color temperatures may be available by special request.

## **Specifications**

Order #:	30027	30025
Model:	ELYWL2-302S	ELYWL2-302C
Lumen Output:	2100 lm	2100 lm
Luminous Efficacy:	105 lm/W	105 lm/W
Beam Angle:	110°	110°
Input Power:	20 W	20 W
Input Voltage:	120-277 Vac	120-277 Vac
Power Factor:	≥90%	≥90%
THD:	<20%	<20%
CCT:	3000 K	4000 K
CRI:	>80	>80
Lifetime:	50000 hours	50000 hours
Warranty:	5 Years	5 Years
Dimmable:	No	No
Operating Temp:	14°F to 122°F	14°F to 122°F
Environment:	Damp Rated	Damp Rated
Weight:	6.1 lbs	6.1 lbs
DLC:	No	No
Dimensions:	48.5"(L)x5.6"(W)x2.0"(H)	48.5"(L)x5.6"(W)x2.0"(H)