

Project:	Catalog#:	Type:
Prepared By:	Notes:	Date:

T-Flex

Energetic LED T-Flex Troffer Series • CCT & Wattage Selectable • 5 Year Limited Warranty



Overview

T-Flex™ is available for color and Lumen selectable as well as fixed CCT models, Plug-n-Play Sensors, and Factory installed Vitality cyan boosting 5000K for Circadian lighting benefits upon requests.

T-Flex™ engineered to meet DLC Standard and DLC Premium 5.1 performance criteria.

Easy field installable accessories such as OCC motion and daylight harvesting with snap in and quick connect wiring, Bluetooth mesh controls (works with google assistant or Alexa) and No need for expensive controls by utilizing on-board 12V power supply. Emergency battery back-up options.

Job site friendly packaging made to be easy to unpack, maximized for spatial efficiency, less boxes less hassle, and a Quick field installable assets such as Driver, 12V PSU for control, Sensor, and Emergency Battery reducing time & labor costs.

Energetic Lighting embarked on a plan to re-engineer products and packaging to reduce its carbon footprint while maintaining uncompromised quality and performance. By configuring the Flex™ in multi-packs and reducing its volume we can increase the number of units we can ship in one container. This reduces the number of containers shipped saving petroleum while decreasing carbon.


Features

- Fixed and Selectable CCT Models 2x2 and 2x4
- Easily convert selectable CCT to Tunable with eZCMD controls
- Vitality Cyan Boosted 5000K technology (Circadian Lighting)
- Lighting Luminaire Level Controls
- Selectable Lumens up to 70000Lm
- Plug-n-Play Motion Sensor and EM for easy field installation
- Multi-Pack 2x2 (4) 2x4 (2)&(4)
- Reduced Profile same classic look
- Easy Job Site friendly packaging Eco-Friendly Packaging


Applications

- Healthcare Facilities
- Offices and Retail spaces
- School & Universities

Highlights



Emergency battery test button and indicator constructed of a flexible printed circuit board that utilized provided adhesive backing to add to the front trim of the fixture. Installs quickly and is plug n play.



Selectable CCT fixtures can be easily turned into linearly tunable fixtures with the optional eZCMD controls (Q4 Launch). Emergency battery and motion sensor options are available.



Energetic Lighting embarked on a plan to re-engineer products and packaging to reduce its carbon footprint. An Eco-friendly packaging.

Load Information

Input Voltage	120-277V 120-347V	
Power Factor	>0.9	
THD	<23%	
Low Temp Start	-20°C (-4°F)	
Max Temp	40°C (104°F)	
Unit Weight	2x2	12.8 lbs
	2x4	25.5 lbs

Shipping Information

Item	Weight	Box Qty.
2x2	55 lbs	4 per case
2x4	55 lbs	2 per case


Are available in single cartons for stock distribution and online sales.

*repack price may be higher

Lumen Maintenance

Housing Type	Ambient Temperature	TM-21 Lumen Maintenance (50,000 hours)	Theoretical L70 (hours)
2x2	30°C	>76%	50,000
2x4	30°C	>76%	50,000

Dimensions



2x2 Models

2x4 Models

Model Ordering Number

Series Prefix	Sizing	Voltage	DLC Class	Lumens	CRI	CCT	Dimming	Power
STA	2	N	P	26E	8	3550	D	S
STA Energetic LED T-Flex Troffer Series	2 2x2 4 2x4	N 120-277V M 120-347V	P Premium S Standard	32E 3200LM 38E 3800LM 44E 4400LM 45E 4500LM 57E 5700LM 65E 6500LM <small>(E does not represent anything at this time)</small>	8 80 CRI	3550 3500K, 4000K, 5000K; 40 4000K	D 0-10V Dimmable	S Selectable Lumens F Fixed Lumens M Motion Sensor

Ordering Examples:

1. For STA4MP57E83550 36, 40, 45W ezWATT Selectable ezCCT 3500K,4000K,5000K 100-277V + 0-10V dimmable

Model#: STA4MP57E83550-DS

STOCK ORDER INFORMATION

2x2 ezCCT & ezWATT Selectable 120-277V, or 120-347V

2x2 Housing	Model Number	Order #	Lumens	Wattage	LPW	CCT	CRI	Voltage	Dimming	DLC	Pallet QTY
	STA2MP32E83550-DF(M)	60101	3200 LM	25W	125	3500K,4000K, 5000K Selectable	80+	120-347V	0-10V	DLC 5.1 P	48
STA2MS45E83550-DF(M)	60102	4500 LM	36W	125	3500K,4000K, 5000K Selectable	80+	120-347V	0-10V	DLC 5.1 S	48	
STA2MP38E83550-DS(M)	60100	3800 LM	21/25/30W	125	3500K,4000K, 5000K Selectable	80+	120-347V	0-10V	DLC 5.1 S	48	

2x4 Fixed Single Color Temp 120-277V, or 120-347V

2x4 Housing	Model Number	Order #	Lumens	Wattage	LPW	CCT	CRI	Voltage	Dimming	DLC	Pallet QTY
	STA4MP32E840-DF(M)	60113	3200 LM	25W	125	4000K	80+	120-347V	0-10V	DLC 5.1 P	TBA
STA4NP45E840-DF(M)	60111	4500 LM	36W	125	4000K	80+	120-277V	0-10V	DLC 5.1 P	TBA	
STA4MP38E840-DS(M)	60112	3800 LM	21/25/30W	125	4000K	80+	120-347V	0-10V	DLC 5.1 P	TBA	
STA4MP57E840-DS(M)	60110	5700 LM	36/40/45W	125	4000K	80+	120-347V	0-10V	DLC 5.1 P	TBA	
STA4MP70E840-DF(M)	60114	7000LM	56W	125	4000K	80+	120-347V	0-10V	DLC 5.1 P	TBA	

2x4 ezCCT & ezWATT Selectable 120-277V, or 120-347V

2x4 Housing	Model Number	Order #	Lumens	Wattage	LPW	CCT	CRI	Voltage	Dimming	DLC	Pallet QTY
	STA4MP32E83550-[D,T]F[M]	60109	3200 LM	25W	125	3500K,4000K, 5000K Selectable	80+	120-347V	0-10V	DLC 5.1 P	TBA
STA4NP45E83550-[D,T]F[M]	60107	4500 LM	36W	125	3500K,4000K, 5000K Selectable	80+	120-277V	0-10V	DLC 5.1 P	TBA	
STA4MP38E83550-DS[M][T]	60108	3800 LM	21/25/30W	125	3500K,4000K, 5000K Selectable	80+	120-347V	0-10V	DLC 5.1 P	TBA	
STA4NP57E83550-DS[M][T]	60106	5700 LM	36/40/45W	125	3500K,4000K, 5000K Selectable	80+	120-277V	0-10V	DLC 5.1 P	TBA	

Optional Accessories

Accessories	Model Number	Order #	Description
	EL-ID8WEM	-	Field installable plug-n-play
	-	-	12V Power Supply for external controls by others



ENERGETIC
L I G H T I N G

T-Flex

Energetic LED T-Flex Troffer Series • CCT & Wattage
Selectable • 5 Year Limited Warranty

NOTES: